

The Original **SUPA® Slickline**

Central Wire Industries UK Ltd. manufactures the original **GD™ - SUPA® Slicklines**. With our production facility in the United Kingdom, we supply our slickline internationally to companies in the oil and gas markets.



CWI
GROUP OF COMPANIES

GD316™
(UNS S31600)

Nom. Composition	%Ni	%Cr	%Mo	%Si	%N	%MN	%P	%S	%C	PRE
	10.0-14.5	16-18	2.0-3.0	<1.0	0.06 max	<2.0	<0.045	<0.010	<0.07	24-29
Sizes	0.072"	0.092"	0.108"	0.125"	0.140"	0.150"	0.160"			
Nom. Break Load	950 lbs	1600 lbs	2200 lbs	3000 lbs	3650 lbs	4100 lbs	4400 lbs			

SUPA 40®
GD22™
(UNS S31803)

Nom. Composition	%Ni	%Cr	%Mo	%Si	%N	%MN	%P	%S	%C	PRE
	4.56-6.5	21-23	2.5-3.5	<1.0	0.14-0.20	<2.0	<0.03	<0.020	<0.03	31.5-37.7
Sizes	0.072"	0.092"	0.108"	0.125"	0.140"	0.150"	0.160"			
Nom. Break Load	950 lbs	1600 lbs	2200 lbs	3000 lbs	3650 lbs	4100 lbs	4400 lbs			

SUPA 75®
GD31Mo™
(UNS N08926)

Nom. Composition	%Ni	%Cr	%Mo	%Cu	%C	%N	%MN	%P	%S	PRE
	24-26	20-21	6.0-6.5	0.5-1.0	<0.02	0.15-0.25	<2.00	<0.03	<0.005	42-47
Sizes	0.072"	0.092"	0.108"	0.125"	0.140"	0.150"	0.160"			
Nom. Break Load	970 lbs	1620 lbs	2170 lbs	2850 lbs	3400 lbs	4020 lbs	4400 lbs			

GD50™
(UNS R30035)

Nom. Composition	%Ni	%Cr	%Mo	%Co	%Ti	%MN	%P	%S	%Si	%C	%B	%Fe	PRE
	33-37	19-21	9-15	BAL	<1.0	<0.15	<0.015	<0.01	<0.15	<0.02	<0.010	<1.0	<50
Sizes	0.072"	0.092"	0.108"	0.125"	0.140"	0.150"	0.160"						
Nom. Break Load	N/A	1680 lbs	2244 lbs	3200 lbs	3500 lbs	N/A	4875 lbs						

SUPA®
GD100™
(UNS S32760)

Nom. Composition	%Ni	%Cr	%Mo	%Si	%N	%MN	%W	%Cu	%C	PRE
	6-8	24-26	3-4	<1	.20-0.30	<1	0.50-1	0.50-1	<0.30	<40
Sizes	0.072"	0.092"	0.108"	0.125"	0.140"	0.150"	0.160"			
Nom. Break Load	N/A	1629 lbs	2200 lbs	2950 lbs	N/A	N/A	N/A			

CWI GD™ - SUPA® SLICKLINES

Strategic stocks held in the UK / USA / UAE.